



M&M PROTEK
since 2005

Ficha Técnica

Sapato S3 SRC ESD Modelo MICRO
Ref.MO100630

Descrição:

- O Monitor Micro é o novo sapato de segurança desportivo fabricado com tecnologia de injeção;
- Sola em poliuretano de dupla densidade com uma dureza de Shore 50 A, que em combinação com a palmilha amovível SS 2.0 resulta num sapato incrivelmente confortável e almofadado com uma excelente absorção de energia;
- Este modelo possui atacadores convencionais;
- Possui uma Língua de fole;
- Interior com tecido que absorve a humidade;
- A gáspea do sapato Micro é produzida em nubuck de vaca, com fita refletora no calcanhar;
- Anti-estático e anti-derrapante;
- Adequado para trabalhos na indústria, transporte e armazém;

Cor: Preto;

Tamanhos: 35 ao 47;

Norma: EN ISO 20345:2011 S3 SRC;



Biqueira em compósito



Anti-perfuração



Anti-estático



Ajuste Normal



EU TYPE EXAMINATION CERTIFICATE

intertek



APPROVED BODY 0362

The safety footwear detailed herein meets the criteria of an EU Type Examination in accordance with Annex V, including the applicable clauses of the Essential Health and Safety Requirements of the PPE Regulation EU 2016/425 for Category II products.

This has been shown through satisfactory testing to EN ISO 20345: 2011 and examination of the Technical File Documentation.

Following an EU Declaration of Product Conformity you are

hereby licensed to mark the product(s) detailed in accordance with Article 17 of the PPE Regulation EU 2016/425

ITS Testing Services (UK) Ltd.
Centre Court
Meridian Business Park
Leicester, LE19 1WD
United Kingdom
Phone: +44 (0)116 263 0330
Fax: +44 (0)116 263 0311



Issued to : BASTAD GRUPPEN AB
Box 1031
262 21 Ängelholm
Sweden

Authorised Representative : BASTAD GRUPPEN AB
Box 1031
262 21 Ängelholm
Sweden

Manufacturer : BASTAD GRUPPEN AB
Box 1031
262 21 Ängelholm
Sweden

Issue Date : 02 September 2019

Expiry Date : 02 September 2024

Certificate No. : LECFI00376087

Product Reference(s) : Micro
Hybrid

Description	: Construction	: PU injection
	Toecap	: Composite toe
	Midsole	: Kevlar
	Last	: HN668
	Sole	: PU/PU
	Mould	: PU006
	Test Report(s)	: See Technical Files
	Size Range	: 36-47
	Category	: S3 SRC

Assessor:  Date: 02/09/2019

Certification Manager:  Date: 02/09/2019

For and on behalf of ITS Testing Services (UK) Limited